

- 2 Sachets Composants passifs PCB
- 2 Sachets Semiconducteurs
- 2 Sachets Accessoires et visserie PCB
- 4 Sachets Condensateurs
- 2 Sachets Accessoires coffret

- |   |                       |
|---|-----------------------|
| 4 | RD139                 |
| 4 | BD139                 |
| 4 | 2SC5200               |
| 4 | 2N4033                |
| 4 | 2SK117-BL             |
| 2 | 2SJ103-BL             |
| 2 | 2SC2240               |
| 2 | μPC1237               |
| 2 | IC Socket 8 pins      |
| 2 | R J103 0.25W 1% RN60D |

- |    |                             |
|----|-----------------------------|
| 4  |                             |
| 1  |                             |
| 1  |                             |
| 10 | 4 Sil-Pad TO-264            |
| 10 | 1 Entretoise nylon MF 15 mm |
| 10 | 1 Entretoise nylon FF 22 mm |
| 2  | 10 Rondelles M3 inox        |
| 4  | 10 Eventails M3 inox        |
| 4  | 10 Ecrous M3 inox           |
| 1  | 2 Vis M3X06 inox            |
| 1  | 4 Vis M3X10 inox            |
| 1  | 4 Vis M3X12 inox            |
| 1  | 1 Clé 6 pans 2 mm           |
| 1  | 1 Clé 6 pans 4 mm           |
| 2  | 1 Soudure Sn60Pb38Cu2 (3 m) |
|    | 1 Gaine thermo 6 mm (2 cm)  |
|    | 1 Mastic (pastille)         |
|    | 2 Plaquettes isolation      |

- |   |                                 |   |                            |
|---|---------------------------------|---|----------------------------|
| 2 | 47K 0.25W 1% RN60D              | 1 | Fusible retardé 1.6A       |
| 4 | 1.5K 0.25W 1% RN60D             | 8 | Diodes 1000V 1A            |
| 2 | 620R 0.25W 1% RN60D             | 4 | Ponts redresseur 20A 1000V |
| 2 | 430R 0.25W 1% RN60D             | 2 | Ponts redresseur 1.5A 200V |
| 2 | 12.1R 0.25W 1% RN60D            | 2 | Régulateurs 12V 1.5A       |
| 4 | 330R 0.75W 1% RN70D             | 2 | Relais 16A                 |
| 4 | 270R 0.25W 1% RN60D             | 4 | 2 200µF 35V 16x31.5        |
| 6 | 121R 0.25W 1% RN60D             | 2 | 100µF 35V 8x11.5 mm        |
| 2 | 100R 0.25W 1% RN60D             | 4 | 4.7µF 25V 20%              |
| 2 | 1.2K 0.25W 1% RN60D             | 2 | 47µF 25V 20%               |
| 8 | 150R 0.25W 1% RN60D             | 2 | 220µF 25V 20%              |
| 4 | 0.22R 5.00W 5% 350ppm           | 2 | 27K 0.25W 2% CCF07         |
| 2 | 200R thermistance               | 2 | 10K 0.25W 2% CCF07         |
| 4 | 50R trimmer 1 ou 3 tours        | 2 | 3.6K 0.25W 2% CCF07        |
| 1 | 2 330pF 50V styrène             | 2 | 100K 0.25W 2% CCF07        |
| 1 | 2 680pF 2KV 10%                 | 2 | 5.6K 0.25W 2% CCF07        |
|   | 8 0.47µF 630V 5% polypro        | 4 | 1K 0.25W 2% CCF07          |
|   | 4 470µF 35V 20% Audio SILMIC II | 4 | Leds rouge                 |
|   | 2 220µF 35V 20% Audio SILMIC II | 2 | IC Socket 8 pins           |
|   | 4 Diodes 1N4148                 | 2 | Dissipateurs dual TO-220   |
|   | 1 Support fusible 5 mm          | 2 | Leds vert / rouge          |
|   | 1 Support fusible couvercle     |   |                            |

- 4 15 000 $\mu$ F 35V 30x40